



FARMALL® UTILITY 95A/105A/115A

SERIES TRACTOR
SPECIFICATIONS



FARMALL UTILITY A SERIES TRACTOR SPECIFICATIONS

MODEL	FARMALL 95A	FARMALL 105A	FARMALL 115A
Operator Station		Cab / Non-cab	
Traction		2WD / MFD	
ENGINE			
Type	Tier 4 B/Final with 4-cylinder, turbocharged & aftercooled, FPT		
Displacement	207.5 in ³ (3 400 cm ³)		
Engine HP*	97	112	120
PTO HP*	78	92	100
Emissions Treatment	Cooled Exhaust Gas Recirculation (CEGR) + Selective Catalytic Reduction (SCR) + Clean Up Catalyst (CUC)		
Fuel System	Electronic high pressure common rail		
Alternator	120 amp		
TRANSMISSION/PTO			
Standard	12 × 12 power shuttle – creeper ready (20 × 20)		
Differential Lock	Limited slip (LSD)		
MFD Engagement	Electro-hydraulic		
PTO Speed (Standard / Optional)	540 @ 1,876 engine rpm / 540/540E @ 1,535 engine rpm or 540/1000 @ 2,125 engine rpm		
AXLES			
Front	2WD or MFD with limited slip		
Rear	Flange		
HYDRAULICS/HITCH			
Type	Open center		
Rear Remotes (Standard / Optional)	2 / 3		
Hydraulic Pump / Flow*	16.9 gal. / min. (64 L / min.)		
3-Point Hitch Category	I/II		
Draft Sensing or Lift Control	Top link sensing		
Standard Lift Capacity @ 24 in. Behind Pin	3,200 lb. (1 451 kg), optional lift cylinder; 7,716 lb. (3 500 kg)		
CAPACITIES			
Fuel Tank (Cab / Non-Cab)	29 gal. (110L) / 23 gal. (90L)		
Diesel Exhaust Fluid Tank	2.9 gallons (11L)		
DIMENSIONS & WEIGHTS			
Wheelbase (2WD / MFD)	91 in. (2 310 mm) / 89 in. (2 260 mm)		
Overall Length (2WD / MFD)	161.6 in. (4 105 mm) / 161.1 in. (4 091 mm)		
Overall Height 2WD (Top of Exhaust)	100.5 in. (2 551 mm)		
Overall Height MFD (Top of Cab)	106 in. (2 690 mm)		
Overall Height to ROPS Pivot (Poultry Version)	68.4 in. (1 737 mm) with 22.5 in. rear tires		
Tractor Weight without Ballast (Cab / Non-Cab 2WD)	8,173 lb. (3 715 kg) / 7,304 lb. (3 320 kg)		
Tractor Weight without Ballast (Cab / Non-Cab MFD)	8,492 lb. (3 860 kg) / 7,689 lb. (3 495 kg)		
TIRES			
Standard (2WD)	Front: 10 - 16 R1; Rear: 18.4 - 30		
Standard (MFD)	Front: 12.4 - 24 R1; Rear: 18.4 - 30		
Optional (2WD)	Front: 7.5 - 16 R1; Rear: 16.9 - 30, Front: 10 - 16 R1; Rear: 16.9 - 34		
Optional (MFD)	Front: 13.6 - 24 R1; Rear: 16.9 - 34, Front: 12.5 / 80; Rear: 19.5L - 24, Front: 11.2 / 24 R1; Rear: 16.9 - 30		
Optional (Poultry Version)	Front: 11.5 / 80; Rear: 500 / 60 - 22.5		

*At 2,300 ERPM rated engine speed

SAFETY NEVER HURTS!™ Always read the Operator's Manual before operating any equipment. Inspect equipment before using it, and be sure it is operating properly. Follow the product safety signs, and use any safety features provided. CNH Industrial America LLC reserves the right to make improvements in design and changes in specifications at any time without notice and without incurring any obligation to install them on units previously sold. Specifications, descriptions and illustrative material herein are as accurate as known at time of publication, but are subject to change without notice. Availability of some models and equipment builds varies according to the country in which the equipment is used.

©2019 CNH Industrial America LLC. All rights reserved. Case IH is a trademark registered in the United States and many other countries, owned by or licensed to CNH Industrial N.V., its subsidiaries or affiliates. Any trademarks referred to herein, in association with goods and/or services of companies other than CNH Industrial America LLC, are the property of those respective companies. Printed in U.S.A. www.caseih.com CIH19110701

